Features / Performance

Specifications

| | |
|---|---|
| Machine Type | Slitter/Cutter/Creaser |
| Paper Size | Width 210mm -370mm |

Length 210mm - 670mm

Minimum output size:slit width 48.0mm x cut length 50.0mm

| | |
|---|---|
| Paper Type | Non coated, Coated, Laminated |
| Margin Slit | Width 3.2mm - 55.0mm from the paper edge |
| Gutter Slit | Width 5mm - 15mm* |

(*Gutter strips wider than 15mm are output on the exit tray.)

| | |
|---|---|
| Min Cut Length | Lead edge cut: 3mm |

Gutter cut: 3mm

Trail edge cut: 5.0mm

| | |
|---|---|
| Document Weight | 110-350gsm |
| Slit - Cut - Crease | Up to 6 slits*, 25cuts, 20 creases / document |

(* Max 8 slits by Optional Slitter Module OSM-02)

| | |
|---|---|
| Speed | 30sheets/ min (A4SEF, 2cuts, 1 crease) |
| Input Tray Capacity | 100mm |
| Stacker Capacity | 140mm |
| PC Interface | USB(Software:PC Controller) |
| Optional Module | Rotary Tool Module (RTM-03), Cross Rotary Tool module (CPM-03), |

Optional Slitter module (OSM-02), Optional PCB Kit (OPK-02)

| | |
|---|---|
| Power | AC100 - 230V 50/60Hz |
| Power Consumption | 4.7 - 1.9 A |

| | |
|---|---|
| Dimension | In use : 2,310mm(W) x 765 mm(D) x 1,110 mm(H) |
| | Folded: 1,650mm(W) × 765mm(D) × 1,110mm(H) |
| Weight | 270kg |