



Features / Performance



Specifications

Machine type Vertical collator

The number of bins	10 bins/tower
Maximum number of towers connectable	6 towers
Feeding system	Belt suction feed system
Conveyance system	Roller belt conveyance system
Maximum paper loading volume	65mm (2.56inches)
Paper size (W x L)	105x148 to 350x610mm (4.13x5.83 to 13.77x24.01inches)
*When the length is 508 or more, width is 200 to 230mm	
Paper weight	Cover sheet Fine quality paper : 52 to 300gsm
Art/Coated paper : 79 to 300gsm	
Inner sheet	Fine quality paper : 52 to 157gsm
Art/Coated paper : 79 to 157gsm	
Paper type	<input type="checkbox"/> Sheet
<input type="checkbox"/> Single-folded (Below 80gsm / within 10 bins)	
<input type="checkbox"/> Cross-folded (Below 80gsm / within 5 bins)	
Maximum Process Speed	10,000sets/h (A5LEF)
Error detection	<input type="checkbox"/> Double-feed
<input type="checkbox"/> Mis-feed	
<input type="checkbox"/> Paper jam	
<input type="checkbox"/> No paper	
<input type="checkbox"/> Conveyance path paper jam	
<input type="checkbox"/> Conveyance path door open/close	
Rating and power consumption	220-240V, 50/60Hz, 5.3A, 980W
Dimensions (W x D x H)	Single tower : 765x830x1,972mm (30.12x32.68x77.64inches)
1 tower+LUL-HM: 1,395x830x1,972mm (54.92x32.68x77.64inches)	
Weight	297kg (654.8lb)
System configuration	

## DBMi Saddle System

